

Hydraulic Body Tray Lifter



Height adjustment by easy foot pedal operation and separate lowering lever

Tray support (closed tub) with 5 cylindrical support rollers lockable by brake operating lever and 1 stop roll at the operation side

Movable by 4 steering wheels (Ø 125 mm), 2 of them are lockable and one with direction lock



Transport roller brake



Foot pedal and lowering lever



Robust corner bumpers

No. 80560
No. 80560/1

For 1 – 4 levels, steel
For 1 – 4 levels, stainless steel AISI 304

Sturdy, torsion-free, welded steel construction, with built-in continuous control of height adjustment by easy foot pedal operation and separate lowering lever. Movable by 4 steering wheels (Ø 125 mm) with robust elastic rubber tires with splash- and dustproof, permanently lubricated ball bearings, 1 with direction lock and 2 with brakes at the operation side. Tray support with 5 cylindrical transport rollers (lockable), coated with non-abrasive and sound-attenuating PVC, with splash- und dustproof, permanently lubricated ball bearings (Ø 37 mm, width 470 mm) and 1 stop roller at the operation side. With removable push handle (height 900 mm).

Technical data:

Length/Width: 2440 x 650 mm

Height min./max.: 305 – 1920 mm

Loading capacity: 200 kg

Weight: 110 kg

Packing dimensions L/W/H: approx. 2600 x 750 x 1150 mm (carton + palette)

Gross weight: 160 kg

Options:

80579

Loading capacity up to 250 kg

80573
80573/1
80574
80574/1

Integrated Digital Body Scales
up to 200 kg
up to 200 kg, calibratable
up to 250 kg
up to 250 kg, calibratable



Packing dimensions with Body Scale: L/W/H: approx. 2600 x 750 x 1300 mm

(design or specifications subject to change without notice)