


Electro - Hydraulic Body Tray Lifter



Transport roller brake



Height adjustment by electro-hydraulic module



Robust corner bumpers

No. 80563
No. 80563/1

For 1 – 4 levels, steel

For 1 – 4 levels, stainless steel AISI 304

Sturdy, torsion-free, welded steel construction, with built-in electro-hydraulic module for continuous control of height adjustment. Movable by 4 steering wheels (Ø 125 mm) with robust elastic rubber tires with splash- and dustproof, permanently lubricated ball bearings, 1 with direction lock and 2 with brakes at the operation side. Tray support with 5 cylindrical transport rollers (lockable), coated with non-abrasive and sound-attenuating PVC, with splash- und dustproof, permanently lubricated ball bearings (Ø 37 mm, width 470 mm) and 1 stop roller at the operation side. With removable push handle (height 900 mm).

Technical data:

Length/Width: 2530 x 650 mm

Height min./max.: 305 – 1920 mm

Loading capacity: 200 kg

Weight: 175 kg

Packing dimensions L/W/H: approx. 2600 x 750 x 1150 mm (carton + palette)

Gross weight: 225 kg

Options:

80573
80573/1

Integrated Digital Body Scales

up to 200 kg

up to 200 kg, calibratable



Packing dimensions with Body Scale: L/W/H: approx. 2600 x 750 x 1300 mm

(design or specifications subject to change without notice)